

**MARİNE LİNE COATING SAN.İÇ VE DIŞ TİC.A.Ş.**

Güzelyalı mah.Kemerköprü mevki Sahilyolu cad.

Yosun sok.No 2 Güzelyalı/Pendik/istanbul

497176

Tel: 0 216 493 37 28

fax : 0 216 493 38 36

Ticaret Sicil: Kadıköy**Ticaret Sic.No:** 549594-Pendik vergi dairesi
612 055 81 92SHIP :
SHIPYARD :
SHIOWNER :
DATE :
DWT :**SHIPYARD EQUIPMENT REQUIREMENTS
HEAT CURE İSTEK FORMU**

ITEMS MADDELER	SIGN FOR APC	SIGN FOR SHIPYARD
<ul style="list-style-type: none">- Gas supply, regulator and vaporiser as sourced from LPG supplier, normally 5000kg filled to 85%.- Gaz tipi/gas type: PROPAN/propane- Tank kapasitesi/tank capacity: 2500/5000kg- Heater system : 150 kg.		
<p>SAFETY PROCEDURE / GUVENLİK PROSEDÜRÜ</p> <ul style="list-style-type: none">- Gaz tankı, kargo tankı, ihtiyaç görülen çalışma sahaları güvenlik kordonuna alınmalı ve uyarı levhaları asılmalı.- Gaz tankı, çalışma sahası, kontrol kabini, ihtiyaç görülen noktalara yangın söndürücü bulundurulmalı- Heat curing operasyonu süresince (24 saat) yangıncı görevlendirilmeli- Heat curing yapılırken güvertede herhangi bir yanıcı madde bulundurulmamalı. <p>* A safety zone have to be establish around the gas tank, cargo tanks and necessary working area on deck. Fire extinguishers have to placed around gas tank, control box, and other critical points. During heat curing operation (24 hour), a fireman patrol have to be charged. During heat curing operation, all flammable material which is on deck have to be removed.</p> <ul style="list-style-type: none">- GAZ TANKI CEVRESİNDE VEYA GEMİ GÜVERTESİNDE SICAK ÇALIŞMA YAPILAMAZ!!!• HOT WORK OPERATION IS PROHIBITED ON DECK OR AROUND GAS TANK!!!		
<ul style="list-style-type: none">- Kontrol kabin panosuna 380volt,250 amper şalterden 4x35kesitli kablo ile besleme verilmeli.- Gaz tankı heater box için 380 volt ,40 amper salterden 4x4kesitli kablo ile besleme verilmeli.- Güverte aydınlatmaları gece devreye alınmalı, heat curing yapılan tankın üzeri seygar projector ile aydınlatılmalı.• Control cabin power supply have to be 380 volt, 250amp with 4x35section electric cable.Gas tank power supply have to be 380 volt, 40 amp with 4x4 section electric cable. All deck light have to be switch on at night and heat curing tank need to portable projector light.- ELEKTRİK KESİNTİSİ OLMAMALI, UYGUN NOKTADAN ELEKTRİK BESLEMESİ VERİLMELİ!!!• ELECTRIC POWER HAVE TO SUPPLY WITHOUT ANY INTERRUPTION!!!		

**MARİNE LİNE COATING SAN.İÇ VE DIŞ TİC.A.Ş.**

Güzelyalı mah.Kemerköprü mevki Sahilyolu cad.

Yosun sok.No 2 Güzelyalı/Pendik/istanbul

497176

Tel: 0 216 493 37 28

fax : 0 216 493 38 36

Ticaret Sicil: Kadıköy**Ticaret Sic.No:** 549594-Pendik vergi dairesi
612 055 81 92

ITEMS MADDELER	SIGN FOR APC	SIGN FOR SHIPYARD
<ul style="list-style-type: none">- Heat curing operasyonu boyunca 24 saat kullanabilecek konumda winç hizmeti olmalı, (4 saat öncesinden winç gereksinimi bildirilecek).- Ön kurulum ve ekipmanların gemiden tahliyesinde winç hizmeti sağlanmalı sağlanmalı.* A crane have to be on stand by 24 during operation for movement of equipment (notification will give 4 hour before). Crane also need to take equipment on deck and give them back.		
<ul style="list-style-type: none">- Heat curing esnasında kütleme yapılan tankların dış hava koşullarından izole edilmeli(yağmur,kar vs.)- Tank üzeri cugulların kapatılması için 20kg cam macunu hazır bulundurulmalı.• Suitable protection shall be erected above the hatch opening of all tanks to be lined. In addition, water guards are to be installed around the entrance holes of tanks being coated to prevent rainwater from draining into the tank. Rain shelters and water guards are to be erected and maintained at all times to provide protection in the event of sudden rainstorms		
<ul style="list-style-type: none">- NO HOT WORK IN AREA OF TANKS BEING HEAT CURED AND ROUTE OF GAS HOSE- HEAT CURING ESNASINDA GÜVERTEDE SICAK ÇALIŞMA YAPILMAMALI		
<ul style="list-style-type: none">- NO DECK PAINT WORK IN AREA OF TANKS BEING HEAT CURED AND ROUTE OF GAS HOSE- HEAT CURING ESNASINDA GÜVERTEDE BOYA YAPILMAMASI		
<ul style="list-style-type: none">- NO WATER IN BALLAST TANKS- HEATCURING ESNASINDA BALAST TANKINDA SU BULUNMAYACAK		
<ul style="list-style-type: none">- HEATCURING ESNASINDA 34*DL 6812 PLAKALI KAMYONETİN TERSANEYE GİRİŞ ÇIKIŞININ SAĞLANMASI		



MARİNE LİNE COATING SAN.İÇ VE DIŞ TİC.A.Ş.

Güzelyalı mah.Kemerköprü mevkii Sahilyolu cad.

Yosun sok.No 2 Güzelyalı/Pendik/istanbul

497176

Tel: 0 216 493 37 28

fax : 0 216 493 38 36

Ticaret Sicil: Kadıköy

Ticaret Sic.No: 549594-

Pendik vergi dairesi
612 055 81 92

CONTACT PERSONS: (24 hours)(Name-Number)

Crane Operator:

Foreman:

Fireman:

Electrician:

Kreyn Operator:

Gemi Yetkilisi:

Yangın Operatörü:

Elektrikçi:

APC MARİNE LİNE
HEAT CURİNG CHİEF
ADEM YALÇIN