



**SECTION 1 – PRODUCT / SUBSTANCE AND COMPANY IDENTIFICATION**

**Product Name:** Marine Line Coating  
**Product Number:** 784  
**Manufacturer:** Advanced Polymer Coatings, LLC  
**Address:** 951 Jaycox Rd. --- Avon, Ohio 44011 U.S.A.  
**Phone Number:** {+01} 440 / 937-6218 [toll free 800-334-7193]  
**Fax Number:** {+01} 440 / 937-5046 [toll free 800-615-0233]  
**CHEMTREC:** {+01} 730 / 527-3887 [toll free 800-424-9300]

**C.A.S. Chemical Name:** Polyglycidal Ether of Poly (4-Hydroxystyrene B)  
**Synonyms:** 4-Glycidal Ether Phenyl Methyl Carbinol Homopolymer  
**Intended Use:** See Technical Data Sheet. For Professional Use Only.  
**Application Method:** See Application Specifications. For Professional Use Only.  
**Previous Revision Date:** February 1, 2001

**HMIS Health Rating** 2                      **Flammability** 2                      **Reactivity** 0

**SECTION 2 – COMPOSITION / INFORMATION OF INGREDIENTS**

#	Chemical Name	CAS Number	%
1.	Polyglycidyl Ether of PHS-N	267414-21-1	40.0 – 75.0
2.	Quartz	14808-60-7	20.0 – 45.0
3.	Xylene	1330-20-7	2.0 – 5.0
4.	Toluene	108-88-3	1.0 – 4.0
5a.	Titanium Dioxide (present in white or gray color only)	13463-67-7	< 3.0
5b.	Red Iron Oxide (present in red color only)	1332-37-2	< 2.0
6.	Fumed Silica, amorphous, hydrophilic	67762-90-7	< 2.0

**OSHA (ACGIH) Exposure Limits**

	PEL		TLV		TWA	
	ppm	mg/m <sup>3</sup>	Ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
1.	N/E	N/E	N/E	N/E	N/E	N/E
2.	N/E	N/E	N/E	N/E	N/E	N/E
3.	100	----	100	----	100	----
4.	200	----	50	188	100	----
5a. / 5b.	N/E	N/E	N/E	N/E	N/E	N/E
6	N/E	N/E	N/E	N/E	N/E	N/E

N/E = Not Established

24 HOUR EMERGENCY NUMBER: 800-424-9300 (toll free within Continental U.S.)  
 703-527-3887 (outside Continental U.S. – may be called collect)  
 PRODUCT INFORMATION: 440-937-6218  
 800-334-7193

---

SECTION 3 – HAZARD IDENTIFICATION

---

<b>Hazards:</b>	Harmful if swallowed. Moderate eye irritant. Skin irritant. May cause skin sensitization. Moderate respiratory tract irritant.
<b>Extinguishing Media:</b>	Carbon Dioxide (CO <sub>2</sub> ), Foam, Dry Chemical or Water Fog
<b>Routes of Exposure</b>	Ingestion Eye Contact Skin Contact
<b>Exposure Standards</b>	No standards established for the product. Maintain air contaminant concentrations in the workplace at the lowest feasible levels.
<b>Health Hazards</b>	Harmful if swallowed. Moderate respiratory tract irritant. Corrosive to eyes. Severe eye irritant. Severe skin irritant. May cause skin sensitization.
<b>Target Organs</b>	Eye, Skin, Respiratory system

**Signs and Symptoms of Exposure (Acute effects)**

Inhalation of vapors may cause irritation in the respiratory tract.

Contact of undiluted product with: Eyes; moderately irritating  
Skin; mildly irritating to skin, prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis.

**Signs and Symptoms of Exposure (Possible longer term effects)**

Repeated and or prolonged exposure may cause allergic reaction and sensitization.

Repeated and or prolonged exposure may result in: adverse respiratory effects (such as cough, tightness of chest or shortness of breath), adverse skin effects (such as rash, irritation or dermatitis).

**Medical Conditions Generally Aggravated by Exposure**

Chronic respiratory disease (e.g. Asthma, Bronchitis, Emphysema)

Eye disease. Skin disorders and Allergies.

**Carcinogens Under OSHA, ACGIH, NTP, IARC, Other**

This product contains no carcinogens in concentrations of 0.1 percent or greater.

---

SECTION 4 – FIRST AID MEASURES

---

**Eye Contact**

Hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Seek medical advice.

**Skin Contact**

Remove product and immediately wash affected area with soap and water. Rinse thoroughly. Remove contaminated clothing and shoes. Launder contaminated clothing prior to reuse. If necessary, seek medical advice.

**Inhalation**

Move patient to fresh air. If breathing has stopped or is labored give assisted respiration (e.g. mouth-to-mouth). Prevent aspiration of vomit. Turn victim's head to the side. Seek medical advice.

**Ingestion**

If conscious, administer water to drink - DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious person. Seek medical advice.

**Note to Physician**

Treat symptomatically as required by the condition of the patient.

---

SECTION 5 – FIRE FIGHTING MEASURES

---

**Flash Point (closed cup)** 154°F. (68°C.)

**Flammable Limits in Air:** Lower: 1  
**% by Volume** Upper: 7

**Autoignition Temperature** 997°F. (535°C.)

**Extinguishing Media**

Carbon Dioxide (CO<sub>2</sub>), Foam, Dry Chemical or Water Fog

**Fire Fighting Instructions**

Isolate the hazard and evacuate the area. As best as possible, stay upwind and fight the fire from the maximum distance. Use water spray to cool containers and fire exposed surfaces. Shut off fuel to fire if possible without hazard.

**Fire Fighting Equipment**

Wear self-contained breathing apparatus. Wear a face shield. Wear complete personal protective equipment including butyl rubber boots, gloves, and body suit.

**Unusual Fire and Explosion Hazards**

None known, handle as a combustible liquid.



---

**SECTION 6 – ACCIDENTAL RELEASE MEASURES**

---

**Spill or Leak Procedures:**

Avoid eye or skin contact. Shut off or remove all ignition sources. Stop the leak, if possible. Construct a dike to prevent spreading. In case of a major spill or spillage in a confined space evacuate the area. Check solvent vapor levels before re-entering.

**Clean-Up Procedures**

Absorb spillage with non-reactive, non-combustible materials, e.g. dry soil, sand, vermiculite. Place in appropriate chemical waste container. Incinerate under controlled conditions and dispose of in an approved landfill. Flush area with water spray. Clean-up personnel must be equipped with self-contained breathing apparatus and butyl rubber protective clothing.

**Other Emergency Advice**

Wear protective clothing, boots, gloves, and eye protection.

---

**SECTION 7 – HANDLING AND STORAGE**

---

**Storage**

Handle containers carefully to prevent damage and spillage.  
Material should be kept in original containers.  
Keep in cool, dry, ventilated storage and in closed container.  
Smoking, high heat and open flames should not be permitted in storage areas.  
Storage area to be adequately ventilated.

**Handling**

Avoid contact with skin or eyes.  
Avoid breathing of vapors.  
Use personal protection as shown in Section 8.  
Handle in well-ventilated workspace.  
When handling, do not eat, drink or smoke.

---

**SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION**

---

<b>General Ventilation:</b>	Required in both external and enclosed areas.	
<b>Local Exhaust:</b>	<b>External Areas:</b>	Recommended
	<b>Enclosed Areas:</b>	Required

---

24 HOUR EMERGENCY NUMBER: 800-424-9300 (toll free within Continental U.S.)  
703-527-3887 (outside Continental U.S. – may be called collect)  
PRODUCT INFORMATION: 440-937-6218  
800-334-7193

<b>Respiratory Protection:</b>	<b>External Areas:</b>	Gas & Vapor removing, air purifying respirator (cartridge)
	<b>Enclosed Areas:</b>	Full face, positive pressure demand type (supplied air mask)
<b>Eye Protection</b>		Chemical goggles or full face shield and safety glasses with side shields
<b>Hand Protection</b>		Impermeable gloves. Neoprene rubber gloves. Cuffed butyl rubber gloves. Nitrile rubber gloves.
<b>Protective Clothing</b>		Impervious clothing. Tyvek or Saranex Suit.
<b>Engineering Controls</b>		No specific controls needed.
<b>Work and Hygienic Controls</b>		Provide readily accessible eye wash stations and safety showers. Wash at the end of each workshift and before eating, smoking, or using the toilet. Promptly remove clothing that becomes contaminated. Discard saturated leather articles.

#### SECTION 9 – TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical Form</b>	Mobile liquid
<b>Color (standard)</b>	White, Gray or Red (based on pigment)
<b>Odor</b>	Aromatic benzene-like odor
<b>pH</b>	CA. 7
<b>Specific Gravity (H<sub>2</sub>O = 1.0)</b>	1.41
<b>Decomposition Temperature:</b>	240°C.
<b>Solubility in Water</b>	Insoluble
<b>Percent Volatiles by Volume:</b>	11% (±3%)
<b>Viscosity:</b>	6,000 cPs (±1,000)

#### SECTION 10 – STABILITY AND REACTIVITY

<b>Chemical Stability:</b>	Stable
<b>Conditions to Avoid:</b>	Avoid storage at elevated temperatures
<b>Incompatibility (Materials to Avoid):</b>	Strong Oxidizers, acids and caustics
<b>Hazardous Polymerization:</b>	Will autopolymerize at very high temperatures
<b>Hazardous Decomposition Products:</b>	Carbon monoxide, Carbon dioxide

24 HOUR EMERGENCY NUMBER: 800-424-9300 (toll free within Continental U.S.)  
 703-527-3887 (outside Continental U.S. – may be called collect)

PRODUCT INFORMATION: 440-937-6218  
 800-334-7193



---

SECTION 11 – TOXICOLOGICAL PROPERTIES

---

<b>Acute Oral Toxicity (LD 50, Rat)</b>	5,000 mg/kg (estimated, no deaths)
<b>Acute Dermal Toxicity (LD 50, Rabbit)</b>	8,000 mg/kg (estimated, no deaths)
<b>Acute Inhalation Toxicity (LC 50, Rat)</b>	No deaths after 8 hour exposure to vapor
<b>Other Acute Effects</b>	No Data
<b>Irritation Effects Data</b>	U.S. EPA – Moderate Irritant (Category III) EU -- Irritant for Skin

---

SECTION 12 – ECOLOGICAL INFORMATION

---

<b>Ecotoxicity</b>	No Data on product itself
<b>Environmental Fate</b>	No Data on product itself
<b>Additional Information</b>	This product should not be allowed to enter drains or water courses.

---

SECTION 13 – DISPOSAL CONSIDERATIONS

---

<b>Waste Disposal</b>	Comply with all Federal, State and Local Regulations.
<b>Disposal Methods</b>	Incinerate under controlled conditions according to Federal, State and Local Environmental Regulations. Dispose of in an approved landfill.

---

SECTION 14 – TRANSPORTATION INFORMATION

---

<b>DOT Class</b>	Not Regulated
<b>RCRA Status</b>	Not a Hazardous Waste under RCRA (40 CFR 261)
<b>CERCLA Status</b>	Not Listed
<b>IMO Shipping Data</b>	Refer to Bill of Lading
<b>ICAO/IATA Shipping Data</b>	Refer to Bill of Lading

---

SECTION 15 – REGULATORY INFORMATION

---

**US FEDERAL REGULATIONS**

**Toxic Substance Control Act (TSCA)**

All components are included in the EPA TSCA Chemical Substance Inventory.

---

24 HOUR EMERGENCY NUMBER: 800-424-9300 (toll free within Continental U.S.)  
703-527-3887 (outside Continental U.S. – may be called collect)  
PRODUCT INFORMATION: 440-937-6218  
800-334-7193



## MATERIAL SAFETY DATA SHEET

### Marine Line Coating 784 – Part A (Resin)

Revision Number 1.5

Revision Date April 2, 2001

---

**OSHA Hazard Communication Standard (29 CFR 1910.1200) hazard class(es)**

Irritant. Sensitizer.

#### STATE REGULATIONS

**Proposition 65 Substances** (*component(s) known to the State of California to cause cancer and/or reproductive toxicity and subject to warning and discharge requirements under the "Safe Drinking Water and Toxic Enforcement Act of 1986"*)

None

**New Jersey Trade Secret Registry Number(s)**

None

#### CANADA

**WHMIS Hazard Classification**

No Information Available

#### EUROPEAN ECONOMIC COMMUNITY (EEC)

**EEC Symbol**

Harmful (Xn)

**EEC Risk (R) Phrases**

May cause sensitization by skin contact (R43).  
Irritating to eyes, respiratory system, and skin  
(R36/37/38). Harmful if swallowed (R22).

**EEC Safety Phrases**

In case of contact with eyes, rinse immediately with  
plenty of water and seek medical advice (S26). Wear  
suitable protective clothing, gloves and eye/face  
protection (S36/37/39). In case of accident or if you  
feel unwell, seek medical advice immediately (show  
the label where possible) (S45).

---

### SECTION 16 – OTHER INFORMATION

---

The information on this MSDS is based upon the present state of our knowledge and on current laws and regulations.

This product should not be used for purposes other than shown in the product data sheet without first obtaining written advice.

It is always the responsibility of the user to take all necessary steps to meet the demands of applicable legislation.

---

24 HOUR EMERGENCY NUMBER: 800-424-9300 (toll free within Continental U.S.)  
703-527-3887 (outside Continental U.S. – may be called collect)  
PRODUCT INFORMATION: 440-937-6218  
800-334-7193